

Even better now!



FLEX

WSE 500

Long-neck sander, Classic Giraffe®



- VE electronic control: with constant speed control and speed pre-selection with adjusting wheel
- Dust extraction system with FLEX clip-on system: brush ring on the sanding head; connector for a FLEX safety vacuum cleaner at the rear end of the guide tube

- Due to the spring suspension, the sanding head adjusts itself perfectly to all unevenness. This ensures for a gentle surface contact and also stops dust escaping
- Effective dust extraction from between the brush ring and the sanding pad (round) and through the 10-hole extraction ports prevents premature clogging of the abrasive and promotes a healthy, dust-free working environment
- Velcro adapter: large surface, cushioned
- Easy guiding: by optimal balance between motor and sanding head
- The universal-joint-mounted sanding head and soft backing pad prevent grooving and scratching and ensures a perfect finish
- Ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting, polishing



WSE 500 **381.306**
with vacuum hose, antistatic

Power input	500 watt
Power output	270 watt
No load speed	1000-1650 rpm
Sanding disc Ø	225 mm
Length	1580 mm
Weight	4.8 kg

Safety vacuum cleaner VCE 45 L AC
with automatic filter cleaning
Order no. 369.802



Velcro sanding paper SELECT




Type/ grit	QP	round Order no.
P 16	10	350.079
P 40	20	370.924
P 60	25	348.503
P 80	25	348.511
P 100	25	348.538
P 120	25	349.216
P 150	25	349.224
P 180	25	349.232
P 220	25	348.546
Mix 5 x P80/100/120/150/180	25	370.932

Carry case



Case can be stored horizontally or vertically.



Order no. 365.327



For proper transport Giraffe® WSE 500 and WS 702 VEA as well as abrasives.



With storage space for auxiliary handle and abrasives in the lid.

Soft sanding pad Ø 225, round



Soft sanding pad between grinding pad and abrasive paper. Ideal for finishing surfaces. Improves the dust extractor action and lengthens the service life of the sanding disks.

Recommendation: work with soft sanding pad for in-between and final sanding involving finer grain. Do not work with soft sand pad for rough sanding involving coarse grain and when using sanding fleece.

QP	Order no.
2	377.848

Velcro backing pad Ø 225, round



Soft. Highly flexible backing pad. Facilitates handling and allows for sensitive working. Prevents damage (swirl marks) when the pad touches the surface. For use with velcro backed abrasives.

QP	Order no.
1	366.862

Medium backing pad for sanding down soft fillers. Velcro system for fixing of abrasives.

QP	Order no.
1	352.306

Hard backing pad with high removal rate, with use with velcro backed abrasives.

QP	Order no.
1	350.362

Brush ring



Stops any unintentional roughening of the surface and ensures an optimal material removal.

Dimensions in mm	QP	Order no.
Ø 225 mm	1	376.248

Bail handle



For effortless working in difficult positions (e.g. overhead work).

QP	Order no.
1	301.825

Antistatic vacuum hose



Antistatic suction hose Ø 32 mm x 4 m with snap coupling and coupling bush for vacuum cleaner incl. universal adapter (320.188) antistatic.



QP	Order no.
1	354.953

Extraction connection



Suitable for vacuum hose with FLEX clip-system. Antistatic equipment. For WSE 500 and WS 702 VEA.



QP	Order no.
1	364.460

Your FLEX dealer