

## FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
D-71711 Steinheim/Murr  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Floor and wall finishing

### WST 1000 FV

Order no. 350.923



#### Renovation-Giraffe® scourer for walls and ceilings

- FV electronic control: constant speed, soft-start and overload protection
- Using a unique telescopic system, the Vario-Giraffe® adapts to your needs. Length adjustable from 1330 mm - 1730 mm. Open telescope lock lever, pull out handle and close lever. Handle rotates through 360°
- Ergonomic design with many different handling possibilities for fatigue-free working. The motor is always kept between the gripping positions, ensuring a perfect balance
- Vacuum dust collection: protects against abrasive dust, reduces disc wear, keeps concrete pores for the new coat open
- Flexible rubber vacuum ring with low-wear metal ring: moves smoothly over the surface and protects against dust and stones flying out
- Dust extraction system: with metal ring on the guard, flexible suction hose from the scouring head to the guide tube. Connection facility at the rear of the telescopic tube for FLEX industrial vacuum cleaner, models S 36, S 47 and S 47 M
- The scourer with universal joint shaft and the new scouring head have been purpose-coordinated. This tool quickly and easily removes burrs and other unevenness from walls and ceilings

Technical attributes	WST 1000 FV
Disc Ø	125 mm
Speed without load	8000 rpm
Power input	1010 watt
Power output	600 watt
Tool fixture	28 mm Ø
Dimensions in mm	1330-1730
Weight	5,50 kg

Standard equipment	
1 FixTec quick-clamp nut M 14	313.459
4 m vacuum hose, 32 mm Ø with positive-lock connector and vac connection, antistatic.	354.953
Padded carry case	1 piece