

Surface finishing Metal and Inox

LE 14-7 125 INOX

Order no. 364.924



1400 watt INOXFLEX, specialist for stainless steels and steel alloys, 125 mm

- VR microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- Highly efficient and resilient motor for more power output
- Special gearbox: special gear ratio for high torque in medium and low speed range. Prevents blue discolouration and distortion due to the development of heat.
- Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- SoftVib handgrip with integrated, patented locknut wrench and vibration damping
- Tool-free adjustment of safety guard
- Spindle lock

Technical attributes	LE 14-7 125 INOX
Max. disc diameter	125 mm
Max. polishing pad diameter	160 mm
No load speed	2100-7500 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Weight	2,4 kg

Standard equipment	
1 guard 125 Ø	274.658
1 SoftVib handle	316.857
1 FixTec quick-clamp nut M 14	313.459

Accessories

Flap disc for metal and stainless steel, cambered



Ideal for flap-grinding steel and stainless steel, high material removal rate, guarantees effortless working without filling pores

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
125 Ø x 22,2	P 40	10	349.917
125 Ø x 22,2	P 60	10	349.925
125 Ø x 22,2	P 80	10	349.933

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Surface finishing Metal and Inox

Thin cutting disc for stainless steel



Straight, for fast low-force cutting. Millimetre-accuracy in cutting, low-burr to no-burr edges. 30% longer service life by packaging in stay-fresh can.

Dimensions QTY/PKG: Order no.

in mm:

125 Ø x 1 x 22,2	10	349.836
---------------------	----	---------

SC-VL polishing flap wheel for metal and stainless steel, cambered



Polishing flap wheel for sanding, cleaning and finishing on stainless steel, steel, titanium alloys, light metals, non-ferrous metals and plastics. Remove any tarnish, flash rust, scale and scratches.

Dimensions Grit: QTY/PKG: Order no.

in mm:

125 Ø x 22,2 coarse	5	367.494
125 Ø x 22,2 medium	5	358.606
125 Ø x 22,2 fine	5	367.486

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Surface finishing Metal and Inox

Fillet disc



Compact fleece discs are made from compressed fleece layers and are ideal for perfect surface finishing. especially good for fillet welds. Because of low heat build up discoloration is avoided. Very long working life. Uses: Cleaning, removing of paint, rust, deburring and finishing. Suitable for soft metals, high alloy steel, titanium alloys, ultra fine grinding in preparation for polishing.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
125 Ø x 6 x 22,2	6 A medium	10	358.711
125 Ø x 6 x 22,2	3 S fine	10	358.703

Grinding disc PyraFLEX



Suitable for all sanding work down to pre-polishing; thanks to the structure, work steps can be leapt over and this reduces the working time. Improves the surface quality, lengthens the service life. For all steels, particularly suitable for stainless steels, titanium, nickel, cobalt and chrome alloys. For removing scratches and mill scale from stainless steel, creation of a grinding pattern according to defined quality criteria (looks, surface finish).

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
125 Ø	A 160 (K 120)	10	364.592
125 Ø	A 65 (K 280)	10	358.797
125 Ø	A 45 (K 400)	10	358.800
125 Ø	A 30 (K 600)	10	358.819

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Surface finishing Metal and Inox

SC-Fleece velcro backed disc



Discs made from synthetic nylon fleece with korund grinding grit. The open structure of the disc prevents clogging and build up of heat, long working life. Suitable for working on steel, rustfree steel, non-ferrous metals and plastics. Uses: Removing discoloration, paint, rust, correcting light surface damage and fine matted surfaces.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
125 Ø	coarse	10	358.614

3 PolishFLEX Disc



Qualified for pre-polishing, polishing of stainless steel and high-gloss and mirror-gloss polishing. The fabric is extremely absorbent and does not clog. Very effective and time-efficient work with high surface quality. Used with polishing pastes and polishing creams.

Dimensions in mm:	QTY/PKG:	Order no.
125 Ø	10	364.606

Carry case



From impact-resistant plastic housing for LE 14-7 125.

QTY/PKG:	Order no.
1	367.192

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Surface finishing Metal and Inox

Polishing paste Poli white



Pre-polishing paste, white, 700 g.

QTY/PKG: **Order no.**

1 **255.004**

Polishing paste Poli blue



High gloss paste blue, 700 g.

QTY/PKG: **Order no.**

1 **255.005**

Polishing cream Poli creme



Finishing cream, box 1 kg.

QTY/PKG: **Order no.**

1 **255.006**

Poli set mini white/blue/creme

Polishing set, consisting of: polishing paste white, polishing paste blue, 100 g each and polishing cream, 50 ml.

QTY/PKG: **Order no.**

365.041

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Surface finishing Metal and Inox

Hook and loop grinding pad "Hook"



Sanding pad with foamed base and hook fasteners. Uniform distribution of pressure for sanding and polishing.

Dimensions	Type:	QTY/PKG:	Order no.
------------	-------	----------	-----------

in mm:

125 Ø x M 14	Velcro hook	1	364.584
--------------	-------------	---	---------