

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Angle grinders

### LE 9-10 125

Order no. 350.672



Technical attributes	LE 9-10 125
Max. disc diameter	125 mm
No load speed	6000-10000 rpm
Power input	900 watt
Power output	500 watt
Tool fixture	M 14
Weight	1,9 kg

#### Universal 900 watt angle grinder, 125 mm

- Microprocessor electronics: with tachogenerator constant speed control, speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- Motor: powerful, strong motor for quick working progress
- With double winding protection from metal dust; reduces motor wear and lengthens service life
- Tool-free adjustment of safety guard
- Side handgrip
- This universal angle grinder is suited for steel/metal surface finishing, for work on the site/renovation as well as for vehicle bodywork and construction firms
- Kickback stop - this shuts down the motor on the disc being blocked

Standard equipment	
1 guard 125 Ø	358.029
1 handle	335.274
1 clamping flange	335.282
1 clamping nut M14	100.080
1 pin wrench	

#### Accessories

#### Flap disc for metal and stainless steel, cambered



Ideal for flap-grinding metals, stainless steel, alloyed and non-alloyed steel, light metals, non ferrous metals, construction steel and cast iron. Removing welding spots and beads, processing welding seams, breaking and rounding edges. High material removal rate, guarantees effortless working without filling pores.

Dimensions in mm:	Grit:	QTY/PKG:	Order no.
125 Ø x 22,2	P 60	10	349.925
125 Ø x 22,2	P 80	10	349.933

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Angle grinders

### Thin cutting disc for stainless steel

---



Straight, for fast low-force cutting of thin-walled pipes, profiles and plates. Reduced cutting pressure and extremely low chipping for cool cutting. Ensures burr-free edges and prevents blue discoloration. 30% longer service life by packaging in stay-fresh can.

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

125 Ø x 1 x 22,2	10	349.836
---------------------	----	---------

### SC-VL polishing flap wheel for metal and stainless steel, cambered

---



Polishing flap wheel for sanding, cleaning and finishing on stainless steel, steel, titanium alloys, light metals, non-ferrous metals and plastics. Remove any tarnish, flash rust, scale and scratches. Remove any tarnish, flash rust, scale and scratches. Preparing, grinding and polishing welds.

**Dimensions Grit: QTY/PKG: Order no.**  
**in mm:**

---

125 Ø x 22,2 coarse	5	367.494
125 Ø x 22,2 medium	5	358.606
125 Ø x 22,2 fine	5	367.486

### Steel wire 0,3 mm

---



Corrugated, mount M 14

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

60 Ø	1	124.516
------	---	---------

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Angle grinders

### Steel wire 0,5 mm

---



Knot-type, mount M 14

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

65 Ø 1 124.524

### Diamantjet - diamond cutting disc, standard, concrete

---



Fast, long-life universal cutting disc, suitable for concrete and stone

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

125 Ø x 22,2 1 349.046

### Diamantjet - diamond cutting disc, premium, tile

---



Fast, long-life tile cutting disc with closed diamond segment. Suitable for cutting all tiles, marble, slate, granite and natural stone. Precision cutting and low-noise

**Dimensions QTY/PKG: Order no.**  
**in mm:**

---

125 Ø x 22,2 1 349.038

**FLEX-Elektrowerkzeuge GmbH**

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**

## Angle grinders

### Carry case

---



Without insert. For the machines L 3709, LE 9-10 125, L 10-10 125 select insert no. 378.305. For the machines OS/OSE 80-2, OD/ODE 100-2, ORE 125-2 select insert no. 379.387.

Size ( W x L x QTY/PKG: H):	Order no.
--------------------------------	-----------

---

360 x 228 x 135	1                      376.094
--------------------	--------------------------------

### Case insert

---

Matching insert for carry case 376.094. For angle grinders L 3709, L 10-10 125 and LE 9-10 125.

QTY/PKG:	Order no.
----------	-----------

---

1	378.305
---	---------